YC4D105-D34

Version No.: 2017V01 Implemented on: 2017-09-01

Prime power: 70 kW @ 1500 r/min

Standby power:77 kW @ 1500 r/min

Emission regulations to be observed:

GB 20891-2014 Stage Ⅲ

ECE R96 Stage ⅢA



(Image shown may not reflect actual engine)

Introduction

YC4D series engine is a classic engine product developed by Yuchai, which is well-known and highly recognized in the market and has market holdings of more than 500,000 sets. YC4D105-D34 engines for generator sets have advantages such as high reliability, durability, energy-saving and environment-friendly, compact structure, strong transient loading capacity and easy maintenance.

Product Features

- The main structures, such as engine body, are time-tested, which ensures the high reliability of the whole engine.
- The design of integrated outlet water header pipe of cylinder head is adopted, which reduces the sealing surface and improves sealing reliability.
- Advanced and mature electronically-control common rail (BOSCH) and high-efficiency turbocharged & intercooled technologies are equipped with, which ensure precise control of fuel-injection quantity and sufficient air intake; and the full combustion, low fuel consumption and less emission of diesel engine under different load conditions are ensured.
- With good transient speed governing performance, and strong loading capability. G3 performance requirements for generator set are met.
- Two-stage diesel filter with alarm function is adopted, which ensures the operating.

Product Service

- Service: Yuchai has built the largest service network in the industry with the minimum service radius, the most extensive “three guarantees” and the shortest response time. 49 global offices are set up, including 14 overseas offices in Europe, Africa and South America etc. Besides, 108 overseas service agents, more than 3,000 service stations and 5,000 sales networks of fittings are established, providing the users with satisfying and considerate services.
- 24h global service hotline: +86 95098.


Engine speed	Application	Standard generator unit output		Engine power			
				Total power		Net power	
r/min		kVA	kW	kW	Ps	kW	Ps
1500	Prime	75	60	70	95	68	92
	Standby	80	64	77	105	74	101

Notes:

1. Prime Power: which corresponds to the basic power (PRP) described in ISO 8528. Implement the maintenance according to the Yuchai's requirement, maximum power of variable load continuous output unlimited time. The average output power shall not exceed 70% of the prime power in every 24 hours of operation.
   Standby Power: In correspondence with the emergency standby power (ESP) stated in ISO 8528. Implement the maintenance according to the Yuchai's requirement, maximum power at a variable load in the event of a main power network failure up to a maximum of 200 hours per year. The average output power shall not exceed 70% of the standby power in every 24 hours of operation.
2. The engine power data stated in the table is the measured performance under the condition stated in ISO 8528-1 and ISO 3046.
3. The power output of the generator unit is calculated according to the efficiency of the AC generator. Thus, it is for reference only.
4. The kVA and kW values are converted as per standard power factor 0.8.
5. The information mentioned above is the latest one, however, the relevant information may be altered after publication.

Engine load	1500 r/min	
	g/（kW·h）	L/h
Standby power	230	21.2
Prime power	234	19.6
75% prime power	241	15.3
50% prime power	252	10.6

Remarks: the diesel oil density is 0.835g/cm^3.



Technical Data

Type	Vertical, in-line, water-cooled, four-stroke
Induction system	Turbocharged
Type of combustion chamber	Direct-injection reentrant ω combustion chamber
Cylinder quantity -Bore× stroke	4-108×115 mm
Number of valve per cylinder.	2
Displacement	4.21L
Compression ratio	16.7:1
Cylinder type	Wet-type cylinder sleeve
Working sequence	1-3-4-2
Fuel supply system	Electronically-control high pressure common rail
Lubrication mode	Combination of pressure and splashing
Starting mode	Electronic
Engine oil capacity	13L
Engine oil and fuel consumption ratio	≤0.2%
Rotation	Anticlockwise (facing the power delivery end)
Minimum no-load speed.	(600～650) r/min
Speed-regulation grade	ISO 8528 G3
Noise *Lp*	≤96dB(A)
Total dry weight	
Engine	370 kg
Radiator	61 kg

The final weight and sizes of the engine varies according to the specific arrangement.

Engine Arrangement

- **Air Intake System**
  Air filter
- **Cooling system**
  Radiator (optional)
- **Electrical device**
  24V/12V electrical system
  Inlet preheater (optional)
- **Fuel system**
  Electronically-control high pressure common rail system
  Fuel Filter(two-stage diesel filter)
- **Lubrication system**
  Engine oil filter
- **Flywheel and flywheel housing**
  SAE 11.5″ flywheel
  SAE 3# flywheel housing
- **Documents**
  Operation Instruction
  Installation Guide
  Parts catalog

Fuel grade: Summer: 0# and 10# ordinary diesel oil of GB 252-2015 premium grade or first grade. Winter: 0#, -10#, -20#, and -35# ordinary diesel oil of GB 252-2015 premium grade or first grade.

Oil brand: 15W-40 in summer; 10W-30 or other environmentally suitable diesel engine oils with the quality grade not lower than Grade CH-4 as provided in GB 11122-2006 in winter.